



C3 PROZESS- UND  
ANALYSENTECHNIK

PRODUKTINFORMATION

# Hot Disk AB TPS 500 S

Wirtschaftlicher Allrounder - kompakt und flexibel



# TPS 500 S

Hot Disk Thermal Constants Analyser



## Thermal Constants Analyser

# TPS 500 S

### Compact and Versatile Thermal Constants Analyser

The TPS 500 S rapidly measures the thermal conductivity, thermal diffusivity and specific heat capacity of solids, powders, pastes, gels and high-viscosity liquids. The instrument has high accuracy and sample geometry is flexible. Sample preparation is kept to a minimum and most materials are tested in less than 60 seconds. This versatile instrument along with the elegant Hot Disk Thermal Analysis software is the ideal measurement apparatus for the small-scale laboratory or a compact and efficient QC testing system.

The user-friendly test and analysis software incorporates tools for scheduled measurements as well as automated temperature control of external devices. Furthermore it includes tools for exporting results to third-party software (MS Excel or raw text), for additional processing or statistical analysis. For precise and automatic temperature readings an optional PT-100 temperature sensor is available.

The TPS 500 S system constitutes a complete package, including everything necessary for making measurements: Core instrument; Isotropic, Slab, One-Dimensional and limited Specific Heat Capacity software modules; three Sensors; Stainless Steel Verification Samples for data validation and a Room-Temperature Sample Holder.



The Hot Disk Sensor

## THERMAL CONSTANTS ANALYSER

# TPS 500 S



### Hot Disk TPS 500 S

<b>Thermal Conductivity</b>	0.03 to 100 W/m/K using standard isotropic method. 5 to 200 W/m/K using slab or one-dimensional methods.
<b>Thermal Diffusivity</b>	0.02 to 40 mm <sup>2</sup> /s using standard isotropic method. 2 to 100 mm <sup>2</sup> /s using slab or one-dimensional methods.
<b>Specific Heat Capacity</b>	0.10 to 4.5 MJ/m <sup>3</sup> K.
<b>Measurement Time</b>	2.5 to 2560 seconds.
<b>Reproducibility</b>	2 % (thermal conductivity). 10 % (thermal diffusivity, sensor radius 6.4 mm). 12 % (volumetric specific heat, sensor radius 6.4 mm)
<b>Accuracy</b>	Better than 5 % (thermal conductivity).
<b>Temperature Range</b> Core Instrument With Furnace With Circulator	-100 °C to 300 °C. Ambient. Ambient to 300 °C. -35 °C to 200 °C.
<b>Power Requirements</b>	Adjusted to the line voltage in the region of use.
<b>Smallest Sample Dimensions</b>	3 mm x 8 mm diameter or square for bulk testing. 0.1 mm x 12 mm diameter or square for slab testing. 10 mm x 5 mm diameter or square for one-dimensional testing.
<b>Largest Sample Size</b>	Unlimited.
<b>Sensor Types Available</b>	Kapton-insulated sensors 7577 (radius 2.0 mm), 5465 (radius 3.2 mm) and 5501 (radius 6.4 mm) with or without cable.



**Hot Disk<sup>®</sup>**

Hot Disk AB  
Chalmers Science Park  
Sven Hultins Gata 9 A  
412 88 Gothenburg  
Sweden

Phone: + 46 31 411 410  
Website: [www.hotdiskinstruments.com](http://www.hotdiskinstruments.com)  
E-mail: [info@hotdisk.se](mailto:info@hotdisk.se)



**C3 PROZESS- UND  
ANALYSETECHNIK**

C3 Prozess- und  
Analysetechnik GmbH  
Peter-Henlein-Straße 20  
D-85540 Haar b. München  
Telefon (089) 45 60 06 70  
Telefax (089) 45 60 06 80  
[info@c3-analysentechnik.de](mailto:info@c3-analysentechnik.de)